NEW SERIES

ALMİN
ARCHITECTURAL SYSTEMS



ROUTE LINE

ART55
YALITIMLI PENCERE KAPI SERİSİ

Insulated Door and Window Series

Almin® Alüminyum Profil Tescilli Markasıdır.

TEKNİK ÖZELLİKLER (Technical Specifications)

KASA DERİNLİĞİ (Frame Depth)	55 mm
KANAT DERİNLİĞİ (Sash Depth)	65 mm
PROFİL ET KALINLIĞI (Profile Wall Thickness)	1,5 /1,6/ 1,8 /2,0 mm
MAKS. CAM KALINLIĞI (Max. Glass Thickness)	36,0 mm
YALITIM BARİYERİ (Thermal Break)	14,8 mm

KULLANIM SEÇENEKLERİ (Application Options)

İÇ AÇILIM PENCERE (Inward Opening Window / Inswing Window)	+
İÇ AÇILIM KAPI (Inward Opening Door / Inswing Door)	+
DIŞ AÇILIM PENCERE (Outward Opening Window / Outswing Window)	+
DIŞ AÇILIM KAPI (Outward Opening Door / Outswing Door)	+
VASİSTAS PENCERE (Bottom-Hung Window / Transom Window)	+
ÇİFT EKSENEL AÇILIM (Tilt & Turn Opening)	+
PVC AKSESUAR (PVC Hardware Compatibility)	+
PARALEL SÜRME (Tilt & Slide / Parallel Sliding)	+
KATLANIR KAPI (Bi-fold Door / Folding Door)	+
PİVOT (Pivot Window)	+

PERFORMANS DEĞERLERİ (Performance Values)

HAVA GEÇİRGENLİĞİ - EN 12207 (Air Permeability)	CLASS 4 (600 Pa)
SU SIZDIRMAZLIK - EN 12208 (Watertightness)	CLASS 9A (600 Pa)
RÜZGAR YÜKÜ DAYANIM - EN 12210 (Wind Load Resistance)	CLASS 4 (1600 Pa)
SEHİM - EN 12210 (Deflection)	CLASS C (L/300)
SİSTEM UF DEĞERİ - EN 10077-2 (System Uf Value (Thermal Transmittance))	3,20 W/m² K

Almin Alüminyum Profil TESCİLLİ MARKASIDIR.
Her hakkı saklıdır; 2025. Almin Alüminyum'un izni olmadan kopya edilemez, çoğaltılamaz ve yayımlanamaz.
Copyright© 2025. All rights reserved. It shall not be reproduced without permission of Almin Aluminium.