



ROUTE

SYSTEMS

FR60

CEPHE

SİSTEMLERİ

FACADE SYSTEMS





TEKNİK ÖZELLİKLER

TECHNICAL PROPERTIES

PROFİL GENİŞLİKLERİ / PROFILE WIDTHS :	60 mm
DİKME DERİNLİKLERİ / MULLION DEPTHS :	50,60,80,100,120,130,140...200,220
KAYIT DERİNLİKLERİ / TRANSOM DEPTHS :	56,66,86,106,126,136,146...206,226
PROFİL ET KALINLIĞI / PROFILE WALL THICKNESS :	1,6mm 2 - 8 mm
MAX. CAM KALINLIĞI / MAX. GLASS THICKNESS :	50 mm
ISI BARIYERLERİ / INSULATION BARS :	10 - 40 mm
ISI YALITIM DEĞERİ (Uf) / THERMAL INSULATION VALUE (Uf) :	1,32 W/m ² K - 1,98 W/m ² K

KULLANIM SEÇENEKLERİ

APPLICATION ALTERNATIVES

KAPAKLI CEPHE / CAPPED CURTAIN WALL :	•
SİLİKON DERZLİ CAM CEPHE / FOUR SIDED SILICONE CURTAIN WALL :	•
YARI KAPAKLI CEPHE / TWO SIDED CURTAIN WALL :	•
DIŞA TERS VASİSTAS G.K. / TOP HUNG OUTWARD OPENING HIDDEN VENT :	•
DIŞA PARALEL AÇILIM G.K. / PARALLEL OUTWARD OPENING HIDDEN VENT :	•

