



ROUTE

SYSTEMS

AST-145HS

KALDIR SÜR

SLIDING(LIFT SLIDES)





TEKNİK ÖZELLİKLER

TECHNICAL PROPERTIES

KASA DERİNLİĞİ / FRAME DEPTH :	1142,5mm 228,5mm
KANAT DERİNLİĞİ / VENT DEPTH :	64 mm
PROFİL ET KALINLIĞI / PROFILE WALL THICKNESS :	1,8 mm-2 mm
MAX. CAM KALINLIĞI / MAX. GLASS THICKNESS :	24mm-47mm
ISI BARIYERLERİ / INSULATION BARS :	28 mm-22mm
ISI YALITIM DEĞERİ (Uf)-EN1077-2 / THERMAL INSULATION VALUE (Uf) :	(Uf): < 2,45 W/m²K

KULLANIM SEÇENEKLERİ

APPLICATION ALTERNATIVES

	PENCERE WINDOW	KAPI DOOR
KALDIR SÜR / SLIDING(LIFT SLIDES) :	●	●
TEK RAYLI KASA / MONORAIL FRAME :	●	●
ÇİFT RAYLI KASA / DUOPLE FRAME :	●	●
ÜÇ RAYLI KASA / THREE RAILED FRAME :	●	●
KENDİNDEN SİNEKLİKLİ KASA / SELF-INSECT SCREEN FRAME :	●	●
GÖMME KASA / CORRUGATED FLAT FLOOR FRAME :	●	●

